



Electrical		SP-100	SP-575	SP-1575	SP-1875	SP-3000	SP-6000	SP-7000	SP-7550	SP-8500	SP-9300	SP-9500
Speed Controller	Weather-proof epoxy encapsulated design with dial speed control	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗
	Variable speed dial controller with digital display for spreading width & digital system status & circuit protection	✗	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗
	Dual independent auger/spinner speed & flow control system digital display with system status & circuit protection	✗	✗	✓	✓	✓	✓	✓	✓	✓	✓	✓
Wiring Harness	12 gauge 2 conductor cable c/w moulded plugs	✗	✓	✓	✓	✓	✓	✗	✓	✓	✓	✓
	Completely loomed 10 gauge GxL high temperature automotive wiring with plugs	✗	✓	✓	✓	✓	✓	✗	✓	✓	✓	✓
Construction		SP-100	SP-575	SP-1575	SP-1875	SP-3000	SP-6000	SP-7000	SP-7550	SP-8500	SP-9300	SP-9500
Frame	Frame heavy duty modular steel frame	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Hopper	One-piece safety yellow high density polyethylene; UV protected	✓	✓	✓ x2	✓ x2	✓ x2	✓ x2	✓	✓ x2	✓ x2	✓ x2	✓ x2
Motor	12-volt sealed direct drive motor	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Spinner Transmission	Maximum torque transmission with bronze gear & grease filled	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Auger-Drive Assembly	Heavy duty steel auger, coupled to maximum torque transmission	✗	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Finish	Electrostatic powder finish	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Mounting	Heavy duty ratchet straps, combined with adjustable stop brackets & bolt-in place rails	✗	✗	✗	✗	✓	✓	✗	✓	✓	✓	✓
Standard Equipment		SP-100	SP-575	SP-1575	SP-1875	SP-3000	SP-6000	SP-7000	SP-7550	SP-8500	SP-9300	SP-9500
Top Screen	8mm steel rod grid	✗	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Weather Cover	Rigid cover c/w securing hooks	✗	✓	✓	✓	✗	✗	✗	✗	✗	✗	✗
Fitted Tarp	Heavy duty c/w bungee tie-down kit	✓	✗	✗	✗	✓	✓	✓	✓	✓	✓	✓
Vibrator	12-volt DC heavy duty vibrator	✗	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Brake Light	Horizontal bar type with lead	✗	✗	✗	✗	✗	✗	✗	✗	✓	✓	✓
Inverted Vee	2 piece assembly for use with 100% salt or 100% sand	✗	✗	✗	✗	✗	✗	✓	✗	✓	✓	✓
Options		SP-100	SP-575	SP-1575	SP-1875	SP-3000	SP-6000	SP-7000	SP-7550	SP-8500	SP-9300	SP-9500
Weatherproof Speed Controller	Epoxy encapsulated variable speed dial controller (D6173T)	✗	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗
Optimum Flow Kit	Additional vibrator & dual pitch baffle improves material flow for optimum performance (OFK-020)	✗	✗	✗	✗	✓	✓	✗	✗	✗	✗	✗
Gate Kit	Stainless steel gate & 3m cable for material calibration & flow control of free-flowing materials (GAK-020)	✗	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗
Adjustable Deflector	Protects foliage & borders from salt damage, & prevents wastage of material by restricting spread width (ADF-020)	✗	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗
AccuSpray	285 litre tank, optional extra 285 litre saddle tanks, can be used for de-icing or for pre-wetting whilst spreading	✗	✗	✗	✗	✗	✗	✗	✗	✓	✓	✓
Tube Restrictor Kit	Two piece restrictor tube for use with free-flowing material (TRK)	✗	✗	TRK-1575	TRK-1875	TRK-3000	TRK-6000	✗	✗	✗	✗	✗